Revision: 28.10.2021



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.05.2022

Version number 2 (replaces version 1)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: FOME FLEX NEUTRAL GLAZING&FAÇADE PREMIUM SILICONE SEALANT
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture

Sealant

Construction chemicals

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
 UAB TEGRA STATE
- · Savanoriu ave 178A, LT-03154 Vilnius, LITHUANIA
- · Tel.:+37052661167
- · www.tegrastate.eu
- · E-mail: info@tegragroup.eu
- · 1.4 Emergency telephone number: European emergency number: 112 (24h)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P273 Avoid release to the environment.

· Additional information:

EUH208 Contains 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.

Contains biocidal products: 2-octyl-2H-isothiazol-3-one, pyrithione zinc

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Determination of endocrine-disrupting properties

CAS: 870-08-6 Dioctyltin oxide

List II

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

CAS: 58190-57-1 EC number: 611-631-1

Reg.nr.: 01-2119982962-22-xxxx

2-propanone, 2,2',2"-[O,O',O"-(ethylsilylidyne)trioxime]

♦ STOT RE 2, H373

<3.5%

(Contd. on page 2)

Printing date 31.05.2022 Version number 2 (replaces version 1) Revision: 28.10.2021

Trade name: FOME FLEX NEUTRAL GLAZING&FAÇADE PREMIUM SILICONE SEALANT

	(Co	ntd. of page 1
CAS: 870-08-6	Dioctyltin oxide STOT SE 2, H371	<0.65%
CAS: 13463-41-7 EINECS: 236-671-3	Pyrithione zinc Acute Tox. 3, H301; Acute Tox. 2, H330; Repr. 1B, H360D; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=1000); Aquatic Chronic 1, H410 (M=10)	<0.023%
CAS: 26530-20-1 EINECS: 247-761-7	2-octyl-2H-isothiazol-3-one	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Wash with plenty of water or water and soap. In cases of sickness seek medical advice (show label if possible).

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Do not induce vomiting.

If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fire with alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet.
- 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon diooxide (CO2).

Carbon monoxide (CO).

Product during a fire will produce dense black smoke.

- · 5.3 Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Cool endangered receptacles with water spray.

GB

Printing date 31.05.2022 Version number 2 (replaces version 1) Revision: 28.10.2021

Trade name: FOME FLEX NEUTRAL GLAZING&FAÇADE PREMIUM SILICONE SEALANT

(Contd. of page 2)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

· 6.2 Environmental precautions:

Do not allow to enter sewers / surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

· Information about fire - and explosion protection:

Protect from heat.

Keep ignition sources away - Do not smoke.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Keep away from water and moisture.

· Information about storage in one common storage facility:

Store away from oxidizers.

Store away from reducing agents.

Do not store together with acids.

Store away from foodstuffs.

· Further information about storage conditions:

Protect from frost.

Store in dry conditions.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 870-08-6 Dioctyltin oxide

WEL Short-term value: 0.2 mg/m³ Long-term value: 0.1 mg/m³

as Sn; Sk

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Do not inhale dust / smoke / mist.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing.

Do not eat, drink, smoke or sniff while working.

Pregnant women should strictly avoid inhalation or skin contact.

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

· Respiratory protection: Not necessary if room is well-ventilated.

(Contd. on page 4)

(Contd. of page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.05.2022 Version number 2 (replaces version 1) Revision: 28.10.2021

Trade name: FOME FLEX NEUTRAL GLAZING&FAÇADE PREMIUM SILICONE SEALANT

· Hand protection

EN 374



Protective gloves

The glove material has to be impermeable and resistant to the product / the substance / the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves

Polyethylene gloves.

Recommended thickness of the material: ≥ 0.02 mm.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

EN 166



Safety glasses

· Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined
 Melting point/freezing point: Not determined

Boiling point or initial boiling point and

boiling range Not determined
• Flammability Not applicable

· Lower and upper explosion limit

Lower: Not determined
Upper: Not determined
Flash point: Not applicable
Decomposition temperature: Not determined

· Viscosity:

Kinematic viscosityDynamic:Not determinedNot determined

· Solubility

· water: Insoluble

· Partition coefficient n-octanol/water (log

value)
Not determined
Not determined

· Density and/or relative density

Density: Not determined
Relative density Not determined
Vapour density Not determined

(Contd. on page 5)

Printing date 31.05.2022 Version number 2 (replaces version 1) Revision: 28.10.2021

Trade name: FOME FLEX NEUTRAL GLAZING&FAÇADE PREMIUM SILICONE SEALANT

(Contd. of page 4)

· 9.2 Other information

· Appearance:

· Form: Paste

· Important information on protection of health

and environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting

• Explosive properties: Product does not present an explosion hazard

Void

Void

· Change in condition

· Evaporation rate Not determined

· Information with regard to physical hazard

classes · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void

· Self-heating substances and mixtures · Substances and mixtures, which emit

flammable gases in contact with water
Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Void

· Desensitised explosives

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- $\cdot \textbf{Respiratory or skin sensitisation} \text{ Based on available data, the classification criteria are not met.} \\$
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 31.05.2022 Version number 2 (replaces version 1) Revision: 28.10.2021

Trade name: FOME FLEX NEUTRAL GLAZING&FAÇADE PREMIUM SILICONE SEALANT

· 11.2 Information on other hazards

· Endocrine disrupting properties

CAS: 870-08-6 Dioctyltin oxide

List II

(Contd. of page 5)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Dispose of in a safe manner in accordance with local / national regulations.

Do not allow to enter surface or ground water.

Assigning a code from the waste catalogue depends on the sector, in which the user operates, as well as on arrangements made between the waste generator and a competent environment protection department.

· Europea	in waste catalogue
15 01 02	plastic packaging

HP14 Ecotoxic

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number		
ADR, IMDG, IATA	Not applicable	
14.2 UN proper shipping name		
ADR, IMDG, IATA	Not applicable	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Not applicable	
14.4 Packing group		
ADR, IMDG, IATA	Not applicable	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk accordi	ng to	
IMO instruments	Not applicable.	

Printing date 31.05.2022 Version number 2 (replaces version 1) Revision: 28.10.2021

Trade name: FOME FLEX NEUTRAL GLAZING&FAÇADE PREMIUM SILICONE SEALANT

· UN "Model Regulation": Not applicable

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

1907/2006/CE Regulation, UK REACH 1272/2008/CE Regulation, GB CLP

2020/878/UE Regulation

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- Regulation (EU) No 649/2012

CAS: 870-08-6 Dioctyltin oxide

Annex I Part 1

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

CAS: 108-88-3 toluene

3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

CAS: 108-88-3 toluene

3

- · Other regulations, limitations and prohibitive regulations No restriction
- Substances of very high concern (SVHC) according to REACH, Article 57 None of the ingredients is listed.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
- H301 Toxic if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H360D May damage the unborn child.
- H371 May cause damage to organs.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- · Version number of previous version: 1
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 8)

(Contd. of page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.05.2022 Version number 2 (replaces version 1) Revision: 28.10.2021

Trade name: FOME FLEX NEUTRAL GLAZING&FAÇADE PREMIUM SILICONE SEALANT

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern SVHC: Substances of Very High Concern VPVB: very Persistent and very Bioaccumulative Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 2: Acute toxicity – Category 2
Skin Corr. 1: Skin corrosion/irritation – Category 1
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Repr. 1B: Reproductive toxicity – Category 1B
CTOT SC 3: Specific toxicit carest stigicity (circle exposure)

STOT SE 2: Specific target organ toxicity (single exposure) – Category 2
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3